## NSN 5305-01-417-3942



Externally Relieved Body Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-417-3942 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.562 inches **Fastener Length:** 1.937 inches **Head Style:** Knurled no. 5 **Head Diameter:** 0.750 inches **Head Height:** 0.438 inches **First Diameter From Head:** Between 0.235 inches and 0.240 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.499 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): **Criticality Code Justification:** Zzzy **Externally Relieved Body Diameter Quantity:** Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Special Test Features:** Special quality control testing **Test Data Document:** 

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Thread Series Designator:**

Unc

#### **Departure From Cited Document:**

As modified by material

### **Reference Number Differentiating Characteristics:**

As differentiated by material which must conform to ships parts control center special quality control provisions

# NSN 5305-01-417-3942

Externally Relieved Body Screw - Page 2 of 2



Shelf Life:	She	lf	Life:
-------------	-----	----	-------

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0