## NSN 5305-01-417-4140

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-417-4140 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.126 inches and 0.166 inches **Fastener Length:** Between 0.547 inches and 0.577 inches **Head Style:** Fillister **Head Diameter:** 0.130 inches **Head Height:** Between 0.068 inches and 0.083 inches **First Diameter From Head:** Between 0.056 inches and 0.066 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.406 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Qq-s-764, 303 cond a federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response or mil-f-14072 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5305-01-417-4140

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.