NSN 5305-01-417-8018

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-417-8018 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.563 inches **Fastener Length:** Between 1.710 inches and 1.750 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.550 inches and 0.562 inches **Head Height:** Between 0.368 inches and 0.375 inches **Internal Drive Style:** Err-090 **Thread Diameter:** Err-060 Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Special Features:** Altered item. Make from ms16997-102 with coating of xlan p-92 primer and 2 coats of xlan black 1070 fluorocarbon. Material: Steel **Material Specification:** Ff-s-86 federal specification single material response **Surface Treatment:** Phosphate zinc and plastic fluorocarbon **Surface Treatment Specification:** Mil-p-16232, ty z, cl 2 military specification 1st treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig:

A003b0

NSN 5305-01-417-8018

Socket Head Cap Screw - Page 2 of 2



Mil-std (military Standard):

Mil-p-16232 spec.