

View Online at <https://aerobasegroup.com/nsn/5305-01-418-3107>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.343 inches and 0.375 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.357 inches and 0.373 inches

**Head Height:**

Between 0.099 inches and 0.110 inches

**Washer Quantity:**

2

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

55000 pounds per square inch

**Hardness Rating:**

38.0 rockwell c primary washer and 46.0 rockwell c primary washer

**Secondary Washer Relationship To Primary Washer:**

Not identical

**Secondary Washer Style:**

Flat

**Primary Washer Outside Diameter:**

0.337 inches

**Secondary Washer Outside Diameter:**

Between 0.029 inches and 0.035 inches

**Primary Washer Style:**

Split helical ring

**Primary Washer Material Thickness:**

0.140 inches

**Secondary Washer Material Thickness:**

Between 0.338 inches and 0.348 inches

**Material:**

Steel comp 1060 primary washer

**Material Specification:**

Qq-s-636 federal specification single material response secondary washer

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification all treatment responses

**Thread Series Designator:**

Unf

**Specification Data:**

80205-nas720 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0