

View Online at <https://aerobasegroup.com/nsn/5305-01-419-0233>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.375 inches

**Fastener Length:**

Between 0.610 inches and 0.655 inches

**Head Style:**

Watertight

**Head Diameter:**

Between 0.282 inches and 0.294 inches

**Head Height:**

Between 0.092 inches and 0.097 inches

**First Diameter From Head:**

Between 0.097 inches and 0.102 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.235 inches and 0.265 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.138 inches

**Features Provided:**

O ring

**Thready Qty Per Inch (tpi):**

32

**Externally Relieved Body Diameter Quantity:**

1

**Special Features:**

O-ring material: fluorosilicone per mil-r-25988.

**Material:**

Steel comp 302 fastener or steel comp 304 fastener or steel comp 305 fastener

**Material Specification:**

Qq-s-763 federal specification all material responses fastener

**Surface Treatment:**

Oxide fastener

**Surface Treatment Specification:**

Mil-c-13924 cl 2 military specification single treatment response fastener

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-13924 spec.