NSN 5305-01-419-0233

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-419-0233 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.375 inches **Fastener Length:** Between 0.610 inches and 0.655 inches **Head Style:** Watertight **Head Diameter:** Between 0.282 inches and 0.294 inches **Head Height:** Between 0.092 inches and 0.097 inches **First Diameter From Head:** Between 0.097 inches and 0.102 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.235 inches and 0.265 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches **Features Provided:** O ring Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity: Special Features:** O-ring material: fluorosilicone per mil-r-25988. Steel comp 302 fastener or steel comp 304 fastener or steel comp 305 fastener **Material Specification:** Qq-s-763 federal specification all material responses fastener **Surface Treatment:** Oxide fastener **Surface Treatment Specification:** Mil-c-13924 cl 2 military specification single treatment response fastener **Thread Series Designator:** Unc Shelf Life:

N/a

NSN 5305-01-419-0233

Externally Relieved Body Screw - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.