NSN 5305-01-419-2405



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-419-2405 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.420 inches and 0.451 inches **Fastener Length:** Between 0.469 inches and 0.500 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.191 inches and 0.225 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 62000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Screw Material Specification:** Fed 66 federal standard all material responses **Screw Surface Treatment:** Oxide **Screw Surface Treatment Specification:** Mil-c-13924 military specification single treatment response Color: Black **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig:

A500d0

NSN 5305-01-419-2405

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-c-13924 spec.