

View Online at <https://aerobasegroup.com/nsn/5305-01-420-1784>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.266 inches

Fastener Length:

Between 0.343 inches and 0.375 inches

Head Style:

Pan no. 2

Head Diameter:

Between 0.306 inches and 0.322 inches

Head Height:

Between 0.085 inches and 0.096 inches

Washer Quantity:

2

Internal Drive Style:

Cross recess type iii

Thread Diameter:

0.164 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

55000 pounds per square inch

Secondary Washer Relationship To Primary Washer:

Not identical

Secondary Washer Style:

Flat

Primary Washer Outside Diameter:

0.296 inches

Secondary Washer Outside Diameter:

Between 0.307 inches and 0.317 inches

Primary Washer Style:

Split helical ring

Primary Washer Material Thickness:

0.040 inches

Secondary Washer Material Thickness:

Between 0.013 inches and 0.019 inches

Material:

Steel comp 1060 primary washer or steel comp 1561 primary washer or steel comp 1566 primary washer or steel comp 1069 primary washer or steel comp 1070 primary washer or steel comp 1071 primary washer or steel comp 1572 primary washer or steel comp 1074 primary washer or steel comp 1075 primary washer or steel comp 1078 primary washer or steel comp 1080 primary washer

Material Specification:

Qq-s-634 federal specification single material response fastener or qq-s-737 federal specification single material response fastener

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification all treatment responses

Thread Series Designator:

Unc

Specification Data:

80205-nas720 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0