

View Online at <https://aerobasegroup.com/nsn/5305-01-420-2989>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.126 inches

**Fastener Length:**

Between 0.157 inches and 0.188 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.357 inches and 0.373 inches

**Head Height:**

Between 0.122 inches and 0.133 inches

**Locking Feature:**

Strip

**Internal Drive Style:**

Cross recess type iii

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Screw Material:**

Steel comp 4140 or steel comp 4340 or steel comp 8740

**Locking Feature Material:**

Plastic polyamide

**Screw Material Specification:**

Mil-s-5656 military specification 1st material response or mil-s-8844 military specification 2nd material response or ams 6414 assn standard single material response or mil-s-6049 military specification 3rd material response

**Locking Feature Material Specification:**

Mil-f-18240 military specification single material response

**Screw Surface Treatment:**

Cadmium and chromate

**Screw Surface Treatment Specification:**

Qq-p-416, type class 2 federal specification all treatment responses

**Bearing Surface Of Head Surface Finish:**

32.0 microinches

**Shank Surface Finish:**

32.0 microinches

**Thread Surface Finish:**

32.0 microinches

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1190 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0

**Mil-std (military Standard):**

Mil-f-18240 spec.