NSN 5305-01-420-9831

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-420-9831 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.234 inches and 0.254 inches **Fastener Length:** 0.312 inches **Head Style:** Hexagon **Head Height:** Between 0.094 inches and 0.108 inches Width Between Flats: Between 0.243 inches and 0.251 inches **First Diameter From Head:** Between 0.058 inches and 0.078 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.117 inches and 0.127 inches **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 40 Hardness Rating: 26.0 rockwell c and 32.0 rockwell c **Externally Relieved Body Diameter Quantity:** Material: Steel comp 8740 **Material Specification:** Ams 6322 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Ams 2400 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-01-420-9831

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0