## NSN 5305-01-421-0482

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-421-0482

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.363 inches
Fastener Length:
Between 1.223 inches and 1.253 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.339 inches and 0.381 inches
Grip Diameter:
Between 0.1890 inches and 0.1895 inches
Shank Unthreaded Hole Diameter:
0.070 inches threads and 0.080 inches threads
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.190 inches
Grip Length:
Between 0.865 inches and 0.885 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Distance From Head Largest Bearing Surface To Shank Hole Center:
1.122 inches threads
Material:
Titanium alloy uns r56400
Material Specification:
Ams 4928 assn standard single material response or ams 4967 assn standard single material response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1580 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

---

## NSN 5305-01-421-0482

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

