NSN 5305-01-421-4215

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-421-4215 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.225 inches **Fastener Length:** 0.375 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.191 inches and 0.225 inches First Diameter From Head: 0.101 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.078 inches and 0.084 inches **Internal Drive Style:** Cross recess type iii **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 80000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Externally Relieved Body Diameter Quantity:** Color: Black Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Surface Treatment:** Paint head **Surface Treatment Specification:** Mil-c-13924 military specification single treatment response fastener **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-01-421-4215

Externally Relieved Body Screw - Page 2 of 2



Demi			

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.