NSN 5305-01-422-1820

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-422-1820 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.156 inches and 0.218 inches **Fastener Length:** Between 0.906 inches and 0.971 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.156 inches and 0.218 inches **Head Height:** Between 0.125 inches and 0.187 inches **Shoulder Diameter:** 0.186 inches first shoulder and 0.187 inches first shoulder **Shoulder Length:** 0.750 inches first shoulder and 0.753 inches first shoulder **Internal Drive Style:** Hexagon Thread Diameter: 0.164 inches Width Across Flats: 0.940 inches Thready Qty Per Inch (tpi): 32 **Shoulder Shape:** Round first shoulder Material: Stainless steel **Material Specification:** Mil-s-21472 military standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35, type 1 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

Unit Of Measure:

NSN 5305-01-422-1820

Shoulder Screw - Page 2 of 2



em			

Yes - demil/mli

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-21472 spec.