Hexagon Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-422-4351

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
1.250 inches
Fastener Length:
Between 2.406 inches and 2.500 inches
Head Height:
Between 0.302 inches and 0.323 inches
Width Between Flats:
Between 0.736 inches and 0.750 inches
Shank Unthreaded Hole Diameter:
0.105 inches threads and 0.113 inches threads
Thread Diameter:
0.500 inches
Thready Qty Per Inch (tpi):
13
Min. Tensile Strength (psi):
150000 pounds per square inch
Hardness Rating:
32.0 rockwell c and 38.0 rockwell c
Distance From Head Largest Bearing Surface To Shank Hole Center:
2.328 inches threads
Material:
Steel
Material Specification:
Sae j429, grade 8 assn standard all material responses
Surface Treatment:
Phosphate zinc
Surface Treatment Specification:
Mil-p-16232, type z, class 2 military specification all treatment responses
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0

Hexagon Head Cap Screw - Page 2 of 2

Mil-std (military Standard):

Mil-p-16232 spec.

