## NSN 5305-01-422-7279

Close Tolerance Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-422-7279



## **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.313 inches and 0.363 inches Fastener Length: Between 0.448 inches and 0.478 inches **Head Style:** Pan **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches Locking Feature: Patch threads **Grip Diameter:** Between 0.1625 inches and 0.1635 inches **Internal Drive Style:** Offset cruciform (torque set) **End Application:** F-16 **Thread Diameter:** 0.164 inches Grip Length: Between 0.115 inches and 0.135 inches Thready Qty Per Inch (tpi): 32 Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium and chromate **Thread Series Designator:** Unjc Shelf Life: N/a Unit Of Measure: **Demilitarization:**

No

---

## NSN 5305-01-422-7279

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

