NSN 5305-01-422-7279

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-422-7279 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.313 inches and 0.363 inches **Fastener Length:** Between 0.448 inches and 0.478 inches **Head Style:** Pan **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches **Locking Feature:** Patch threads **Grip Diameter:** Between 0.1625 inches and 0.1635 inches **Internal Drive Style:** Offset cruciform (torque set) **End Application:** F-16 **Thread Diameter:** 0.164 inches **Grip Length:** Between 0.115 inches and 0.135 inches Thready Qty Per Inch (tpi): 32 Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 **Surface Treatment:** Cadmium and chromate **Thread Series Designator:** Unjc Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-01-422-7279

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0