NSN 5305-01-422-8260

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-422-8260 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.200 inches **Fastener Length:** Between 0.219 inches and 0.250 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.178 inches and 0.183 inches **Head Height:** Between 0.059 inches and 0.069 inches **Internal Drive Style:** Torque set **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Screw Material:** Steel comp 4140 or steel comp 4340 or steel comp 8740 **Screw Material Specification:** Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification all treatment responses **Thread Series Designator:** Unjc **Specification Data:** 80205-nas1101 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Fiig:

No

A500d0

NSN 5305-01-422-8260

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-5626 spec.