## NSN 5305-01-423-2335

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-423-2335

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 1.700 inches and 1.750 inches
Fastener Length:
Between 2.234 inches and 2.281 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.365 inches and 0.375 inches
Head Height:
Between 0.244 inches and 0.250 inches
Hole Diameter:
Between 0.061 inches and 0.067 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.250 inches
Width Across Flats:
Between 0.1875 inches and 0.1900 inches
Hole Quantity:
6
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Hole Configuration Style:
Round internal hexagon
Material:
Iron alloy 660
Material Specification:
Ams 5731 assn standard single material response or ams 5737 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unrf

## NSN 5305-01-423-2335

Socket Head Cap Screw - Page 2 of 2



	s	pec	ific	atic	n D	ata	:
--	---	-----	------	------	-----	-----	---

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0