## NSN 5305-01-423-2342

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-423-2342

Thread Class:			
3a			
Thread Direction:			
Right-hand			
Thread Length:			
0.688 inches			
Fastener Length:			
Between 0.719 inches and 0.750 inches			
Head Style:			
Flat chamfer			
Head Diameter:			
Between 0.265 inches and 0.270 inches			
Head Height:			
Between 0.088 inches and 0.102 inches			
Hole Diameter:			
Between 0.034 inches and 0.042 inches			
Internal Drive Style:			
Torque set			
Thread Diameter:			
0.164 inches			
Hole Quantity:			
2			
Thready Qty Per Inch (tpi):			
32			
Min. Tensile Strength (psi):			
160000 pounds per square inch			
Screw Material:			
Iron alloy 660			
Screw Material Specification:			
Ams 5731 assn standard single material response or ams 5737 assn standard single material response			
Screw Surface Treatment:			
Passivate			
Screw Surface Treatment Specification:			
Qq-p-35 federal specification single treatment response			
Head Hole Configuration Style:			
Round longitudinal hole			
Bearing Surface Of Head Surface Finish:			
32.0 microinches			
Thread Surface Finish:			
32.0 microinches			
Thread Series Designator:			
Unjc			

## NSN 5305-01-423-2342

Machine Screw - Page 2 of 2



Spe	cific	ation	Data:
-----	-------	-------	-------

80205-nas1101 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A500d0