## NSN 5305-01-423-2630

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-423-2630 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.391 inches **Fastener Length:** Between 2.501 inches and 2.531 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.752 inches and 0.762 inches **Grip Diameter:** Between 0.3731 inches and 0.3737 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.375 inches **Grip Length:** Between 2.115 inches and 2.135 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp 4340 or steel comp 8735 or steel comp 4140 or steel comp 8740 **Material Specification:** Ams 498 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, ty2, cl2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1206 professional/industrial association standard Shelf Life:

N/a **Unit Of Measure:** 

## NSN 5305-01-423-2630

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0