## NSN 5305-01-423-2630

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-423-2630

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.391 inches
Fastener Length:
Between 2.501 inches and 2.531 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.752 inches and 0.762 inches
Grip Diameter:
Between 0.3731 inches and 0.3737 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.375 inches
Grip Length:
Between 2.115 inches and 2.135 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Steel comp 4340 or steel comp 8735 or steel comp 4140 or steel comp 8740
Material Specification:
Ams 498 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, ty2, cl2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1206 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

---

## NSN 5305-01-423-2630

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

