NSN 5305-01-423-2633

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-423-2633

view Offilitie at https://aerobasegroup.com/his//3000-01-420-2000
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.514 inches and 0.625 inches
Fastener Length:
0.625 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.457 inches and 0.469 inches
Head Height:
Between 0.306 inches and 0.312 inches
Locking Feature:
Pellet threads or patch threads or strip threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.312 inches
Width Across Flats:
Between 0.250 inches and 0.253 inches
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
39.0 rockwell c fastener and 45.0 rockwell c fastener
Minimum Yield Strength:
155000 pounds per square inch
Product Name:
Navy special project
Material:
Steel uns k03104 fastener
Material Specification:
Astm a574 assn standard single material response fastener
Thread Series Designator:
Unrc
Specification Data:
80205-nas1352 professional/industrial association standard
Shelf Life:

N/a

NSN 5305-01-423-2633

Socket Head Cap Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0