NSN 5305-01-423-5051

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-423-5051 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.250 inches and 0.266 inches **Fastener Length:** Between 1.812 inches and 1.875 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.370 inches and 0.380 inches **Head Height:** Between 0.422 inches and 0.453 inches **First Diameter From Head:** Between 0.125 inches and 0.135 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.406 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Product Name:** Navy special project Material: Steel comp 304 **Material Specification:** Qq-s-763 cond a federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072 e300 military specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-01-423-5051

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.