

View Online at <https://aerobasegroup.com/nsn/5305-01-424-6045>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.348 inches and 0.378 inches

Fastener Length:

Between 0.660 inches and 0.690 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.258 inches and 0.305 inches

Grip Diameter:

Between 0.188 inches and 0.189 inches

Internal Drive Style:

Offset cruciform (torque set)

End Application:

F-16

Thread Diameter:

0.190 inches

Grip Length:

Between 0.302 inches and 0.322 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 49.0 rockwell c

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Special Features:

Surface treatment is also dry film lube

Material:

Steel comp h11

Material Specification:

Ams6487 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Nas672 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0