

View Online at <https://aerobasegroup.com/nsn/5305-01-424-6045>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.348 inches and 0.378 inches

**Fastener Length:**

Between 0.660 inches and 0.690 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.258 inches and 0.305 inches

**Grip Diameter:**

Between 0.188 inches and 0.189 inches

**Internal Drive Style:**

Offset cruciform (torque set)

**End Application:**

F-16

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.302 inches and 0.322 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Hardness Rating:**

46.0 rockwell c and 49.0 rockwell c

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Special Features:**

Surface treatment is also dry film lube

**Material:**

Steel comp h11

**Material Specification:**

Ams6487 assn standard single material response

**Surface Treatment:**

Aluminum

**Surface Treatment Specification:**

Nas672 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0