NSN 5305-01-424-8833

Machine Screw - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-424-8833

3aThread Direction:Right-handThread Length:1.375 inchesFastener Length:Between 1.313 inches and 1.375 inchesHead Style:PanHead Diameter:Between 0.306 inches and 0.322 inchesHead Height:Between 0.105 inches and 0.115 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.164 inchesThready Qty Per Inch (tpi):32Product Name:Navy special projectScrew Material:Iron alloy 660Screw Surface Treatment:Cadmium and chromateThread Series Designator:UnjcSpecification Data:80205-nas1190 professional/industrial association standardSheff Life:N/aUnt Of Measure:
Right-hand Thread Length: 1.375 inches Fastener Length: Between 1.313 inches and 1.375 inches Head Style: Pan Head Diameter: Between 0.306 inches and 0.322 inches Head Height: Between 0.105 inches and 0.115 inches Head Height: Cross recess type 1 Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Product Name: Navy special project Screw Material: Iron alloy 660 Screw Material Specification: Ams5737 assn standard single material response Screw Surface Treatment: Cadmium and chromate Thread Series Designator: Unjc Specification Data: 80205-nas1190 professional/industrial association standard Shelf Life: N/a
Thread Length: 1.375 inches Fastener Length: Between 1.313 inches and 1.375 inches Head Style: Pan Head Diameter: Between 0.306 inches and 0.322 inches Head Height: Between 0.105 inches and 0.115 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Product Name: Navy special project Screw Material: Iron alloy 660 Screw Material Specification: Ams5737 assn standard single material response Screw Surface Treatment: Cadmium and chromate Thread Series Designator: Unjc Specification Data: 80205-nas1190 professional/industrial association standard Shelf Life: N/a
Thread Length: 1.375 inches Fastener Length: Between 1.313 inches and 1.375 inches Head Style: Pan Head Diameter: Between 0.306 inches and 0.322 inches Head Height: Between 0.105 inches and 0.115 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Product Name: Navy special project Screw Material: Iron alloy 660 Screw Material Specification: Ams5737 assn standard single material response Screw Surface Treatment: Cadmium and chromate Thread Series Designator: Unjc Specification Data: 80205-nas1190 professional/industrial association standard Shelf Life: N/a
1.375 inches Fastener Length: Between 1.313 inches and 1.375 inches Head Style: Pan Head Diameter: Between 0.306 inches and 0.322 inches Head Height: Between 0.105 inches and 0.115 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Product Name: Navy special project Screw Material: Iron alloy 660 Screw Material Specification: Ams5737 assn standard single material response Screw Surface Treatment: Cadmium and chromate Thread Series Designator: Unjc Specification Data: 80205-nas1190 professional/industrial association standard Shelf Life: N/a
Between 1.313 inches and 1.375 inches Head Style: Pan Head Diameter: Between 0.306 inches and 0.322 inches Head Height: Between 0.105 inches and 0.125 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Product Name: Navy special project Screw Material: Iron alloy 660 Screw Material Specification: Ams5737 assn standard single material response Screw Surface Treatment: Cadmium and chromate Thread Series Designator: Unjc Specification Data: 80205-nas1190 professional/industrial association standard Shelf Life: N/a
Between 1.313 inches and 1.375 inches Head Style: Pan Head Diameter: Between 0.306 inches and 0.322 inches Head Height: Between 0.105 inches and 0.125 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Product Name: Navy special project Screw Material: Iron alloy 660 Screw Material Specification: Ams5737 assn standard single material response Screw Surface Treatment: Cadmium and chromate Thread Series Designator: Unjc Specification Data: 80205-nas1190 professional/industrial association standard Shelf Life: N/a
Pan Head Diameter: Between 0.306 inches and 0.322 inches Head Height: Between 0.105 inches and 0.115 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Product Name: Navy special project Screw Material: Iron alloy 660 Screw Material Specification: Ams5737 assn standard single material response Screw Surface Treatment: Cadmium and chromate Thread Series Designator: Unjc Specification Data: 80205-nas1190 professional/industrial association standard Shelf Life: N/a
Pan Head Diameter: Between 0.306 inches and 0.322 inches Head Height: Between 0.105 inches and 0.115 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Product Name: Navy special project Screw Material: Iron alloy 660 Screw Material Specification: Ams5737 assn standard single material response Screw Surface Treatment: Cadmium and chromate Thread Series Designator: Unjc Specification Data: 80205-nas1190 professional/industrial association standard Shelf Life: N/a
Between 0.306 inches and 0.322 inches Head Height: Between 0.105 inches and 0.115 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Product Name: Navy special project Screw Material: Iron alloy 660 Screw Material Specification: Ams5737 assn standard single material response Screw Surface Treatment: Cadmium and chromate Thread Series Designator: Unjc Specification Data: 80205-nas1190 professional/industrial association standard Shelf Life: N/a
Head Height: Between 0.105 inches and 0.115 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Product Name: Navy special project Screw Material: Iron alloy 660 Screw Material Specification: Ams5737 assn standard single material response Screw Surface Treatment: Cadmium and chromate Thread Series Designator: Unjc Specification Data: 80205-nas1190 professional/industrial association standard Shelf Life: N/a
Between 0.105 inches and 0.115 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Product Name: Navy special project Screw Material: Iron alloy 660 Screw Material Specification: Ams5737 assn standard single material response Screw Surface Treatment: Cadmium and chromate Thread Series Designator: Unjc Specification Data: 80205-nas1190 professional/industrial association standard Shelf Life: N/a
Between 0.105 inches and 0.115 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Product Name: Navy special project Screw Material: Iron alloy 660 Screw Material Specification: Ams5737 assn standard single material response Screw Surface Treatment: Cadmium and chromate Thread Series Designator: Unjc Specification Data: 80205-nas1190 professional/industrial association standard Shelf Life: N/a
Cross recess type 1 Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Product Name: Navy special project Screw Material: Iron alloy 660 Screw Material Specification: Ams5737 assn standard single material response Screw Surface Treatment: Cadmium and chromate Thread Series Designator: Unjc Specification Data: 80205-nas1190 professional/industrial association standard Shelf Life: N/a
Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Product Name: Navy special project Screw Material: Iron alloy 660 Screw Material Specification: Ams5737 assn standard single material response Screw Surface Treatment: Cadmium and chromate Thread Series Designator: Unjc Specification Data: 80205-nas1190 professional/industrial association standard Shelf Life: N/a
0.164 inches Thready Qty Per Inch (tpi): 32 Product Name: Navy special project Screw Material: Iron alloy 660 Screw Material Specification: Ams5737 assn standard single material response Screw Surface Treatment: Cadmium and chromate Thread Series Designator: Unjc Specification Data: 80205-nas1190 professional/industrial association standard Shelf Life: N/a
Thready Qty Per Inch (tpi): 32 Product Name: Navy special project Screw Material: Iron alloy 660 Screw Material Specification: Ams5737 assn standard single material response Screw Surface Treatment: Cadmium and chromate Thread Series Designator: Unjc Specification Data: 80205-nas1190 professional/industrial association standard Shelf Life: N/a
32 Product Name: Navy special project Screw Material: Iron alloy 660 Screw Material Specification: Ams5737 assn standard single material response Screw Surface Treatment: Cadmium and chromate Thread Series Designator: Unjc Specification Data: 80205-nas1190 professional/industrial association standard Shelf Life: N/a
Product Name: Navy special project Screw Material: Iron alloy 660 Screw Material Specification: Ams5737 assn standard single material response Screw Surface Treatment: Cadmium and chromate Thread Series Designator: Unjc Specification Data: 80205-nas1190 professional/industrial association standard Shelf Life: N/a
Navy special project Screw Material: Iron alloy 660 Screw Material Specification: Ams5737 assn standard single material response Screw Surface Treatment: Cadmium and chromate Thread Series Designator: Unjc Specification Data: 80205-nas1190 professional/industrial association standard Shelf Life: N/a
Screw Material: Iron alloy 660 Screw Material Specification: Ams5737 assn standard single material response Screw Surface Treatment: Cadmium and chromate Thread Series Designator: Unjc Specification Data: 80205-nas1190 professional/industrial association standard Shelf Life: N/a
Iron alloy 660 Screw Material Specification: Ams5737 assn standard single material response Screw Surface Treatment: Cadmium and chromate Thread Series Designator: Unjc Specification Data: 80205-nas1190 professional/industrial association standard Shelf Life: N/a
Screw Material Specification: Ams5737 assn standard single material response Screw Surface Treatment: Cadmium and chromate Thread Series Designator: Unjc Specification Data: 80205-nas1190 professional/industrial association standard Shelf Life: N/a
Ams5737 assn standard single material response Screw Surface Treatment: Cadmium and chromate Thread Series Designator: Unjc Specification Data: 80205-nas1190 professional/industrial association standard Shelf Life: N/a
Screw Surface Treatment: Cadmium and chromate Thread Series Designator: Unjc Specification Data: 80205-nas1190 professional/industrial association standard Shelf Life: N/a
Cadmium and chromate Thread Series Designator: Unjc Specification Data: 80205-nas1190 professional/industrial association standard Shelf Life: N/a
Thread Series Designator: Unjc Specification Data: 80205-nas1190 professional/industrial association standard Shelf Life: N/a
Unjc Specification Data: 80205-nas1190 professional/industrial association standard Shelf Life: N/a
Specification Data: 80205-nas1190 professional/industrial association standard Shelf Life: N/a
80205-nas1190 professional/industrial association standard Shelf Life: N/a
Shelf Life: N/a
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A500d0