NSN 5305-01-424-9910

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-424-9910 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.378 inches and 0.428 inches **Fastener Length:** Between 1.200 inches and 1.230 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.350 inches and 0.399 inches **Grip Diameter:** Between 0.248 inches and 0.249 inches **Internal Drive Style:** Offset cruciform (torque set) **End Application:** F16acft **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.802 inches and 0.822 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** 100.0 degrees **Surface Finish:** 32.0 microinches threads **Special Features:** Drilled threads Material: Steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 **Surface Treatment:** Cadmium and chromate **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5305-01-424-9910

Close Tolerance Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0