## NSN 5305-01-425-0113

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-425-0113 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.280 inches and 0.320 inches **Fastener Length:** Between 0.820 inches and 0.840 inches **Head Style:** Knurled no. 5 **Head Diameter:** 0.500 inches **Head Height:** Between 0.360 inches and 0.390 inches **First Diameter From Head:** 0.235 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.520 inches **Point Style:** Cone **Internal Drive Style:** Slot **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 18 **Criticality Code Justification: Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Astm a581 assn standard single material response **Surface Treatment: Passivate Special Test Features:** Special quality control testing **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response

Unc

**Thread Series Designator:** 

## NSN 5305-01-425-0113

Externally Relieved Body Screw - Page 2 of 2



Departure	From	Cited	<b>Document:</b>
Departure		Oitcu	Document.

As modified by material

## **Reference Number Differentiating Characteristics:**

As differentiated by material which must conform to ships parts control center special quality control provisions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0