NSN 5305-01-425-2426

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-425-2426 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.150 inches and 0.156 inches **Fastener Length:** Between 0.334 inches and 0.346 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.372 inches and 0.374 inches **Head Height:** 0.040 inches **Shoulder Diameter:** 0.278 inches first shoulder and 0.280 inches first shoulder **Shoulder Length:** 0.184 inches first shoulder and 0.190 inches first shoulder **Internal Drive Style:** Torque **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 40.0 rockwell c and 45.0 rockwell c **Shoulder Shape:** Round first shoulder **Special Features:** 63.0 micro finish on side of head and shoulder Material: Steel comp 630 **Material Specification:** Ams 5643, cond a assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35, type 1 federal specification single treatment response **Thread Series Designator:** Unf

Shelf Life:

N/a

NSN 5305-01-425-2426

Shoulder Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0