NSN 5305-01-425-2430

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-425-2430 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.450 inches **Fastener Length:** Between 0.470 inches and 0.500 inches **Head Style:** Knurled no. 5 **Head Diameter:** Between 0.198 inches and 0.205 inches **Head Height:** Between 0.121 inches and 0.125 inches **Locking Feature:** Patch threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.125 inches Width Across Flats: 0.094 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 190000 pounds per square inch Hardness Rating: 38.0 rockwell c and 43.0 rockwell c Minimum Yield Strength: 170000 pounds per square inch Material: Steel uns k03104 fastener **Material Specification:** Mil-f-18240 military specification single material response locking feature **Surface Treatment:** Cadmium fastener **Surface Treatment Specification:** Qq-p-416, type 1 federal specification single treatment response fastener or ams 2400 assn standard single treatment response fastener **Thread Series Designator:** Unrc

Shelf Life:

N/a

NSN 5305-01-425-2430

Socket Head Cap Screw - Page 2 of 2



	• -		
In	ıŧ	()t	Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-18240 spec.