NSN 5305-01-426-1248

Setscrew - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5305-01-426-1248

2a
Thread Direction:
Right-hand
Thread Length:
Between 0.497 inches and 0.503 inches
Fastener Length:
0.750 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.365 inches and 0.375 inches
Head Height:
Between 0.244 inches and 0.250 inches
Point Length:
Between 0.247 inches and 0.253 inches
Point Diameter:
Between 0.185 inches and 0.190 inches
Point Style:
Dog
Internal Drive Style:
Hexagon
Thread Diameter:
0.250 inches
Width Across Flats:
Between 0.188 inches and 0.190 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell c
Minimum Yield Strength:
30000 pounds per square inch
Special Features:
ALTE-R,-MAK-EFRO
Material:
Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316
Material Specification:
Fed 66, 300 series federal standard all material responses
Surface Treatment:
Passivate

NSN 5305-01-426-1248

Setscrew - Page 2 of 2



Surface Treatment Speci

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0