

View Online at <https://aerobasegroup.com/nsn/5305-01-429-7291>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.290 inches and 0.310 inches

Fastener Length:

Between 0.290 inches and 0.310 inches

Head Style:

Hexagon

Head Height:

Between 0.134 inches and 0.138 inches

Width Between Flats:

Between 0.244 inches and 0.250 inches

Internal Drive Style:

Hexagon

Material Accommodated Thickness:

Between 0.219 inches and 0.250 inches

Thread Diameter:

0.190 inches

Width Across Flats:

Between 0.142 inches and 0.144 inches

Thread Qty Per Inch (tpi):

32

Special Features:

Captivating bushing: steel qq-s-764, class 303; passivated, qq-p-35; shear bushing: steel 17-4ph, ams 5622; passivated, qq-p-35; sleeve: steel, qq-s-763, class 304; passivated qq-p-35

Material:

Steel primary washer

Material Specification:

Qq-s-423, cond b federal specification single material response spring

Surface Treatment:

Passivate spring

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification all treatment responses primary washer

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5059 spec.