

View Online at <https://aerobasegroup.com/nsn/5305-01-429-7291>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.290 inches and 0.310 inches

**Fastener Length:**

Between 0.290 inches and 0.310 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.134 inches and 0.138 inches

**Width Between Flats:**

Between 0.244 inches and 0.250 inches

**Internal Drive Style:**

Hexagon

**Material Accommodated Thickness:**

Between 0.219 inches and 0.250 inches

**Thread Diameter:**

0.190 inches

**Width Across Flats:**

Between 0.142 inches and 0.144 inches

**Thready Qty Per Inch (tpi):**

32

**Special Features:**

Captivating bushing: steel qq-s-764, class 303; passivated, qq-p-35; shear bushing: steel 17-4ph, ams 5622; passivated, qq-p-35; sleeve: steel, qq-s-763, class 304; passivated qq-p-35

**Material:**

Steel primary washer

**Material Specification:**

Qq-s-423, cond b federal specification single material response spring

**Surface Treatment:**

Passivate spring

**Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification all treatment responses primary washer

**Thread Series Designator:**

Unjc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5059 spec.