

View Online at <https://aerobasegroup.com/nsn/5305-01-430-2100>

Thread Direction:

Right-hand

Thread Length:

Between 0.395 inches and 0.425 inches

Fastener Length:

Between 0.485 inches and 0.515 inches

Head Style:

Spade

Head Height:

Between 0.365 inches and 0.395 inches

Head Length:

Between 0.365 inches and 0.395 inches

Width Between Flats:

Between 0.175 inches and 0.205 inches

Internal Drive Style:

W/o internal drive

End Application:

F-18

Thread Diameter:

0.190 inches

Nonstandard Thread Pitch Diameter:

+0.1587/+0.1597 inches

Thready Qty Per Inch (tpi):

32

Hardness Rating:

Between 32.0 rockwell c and 38.0 rockwell c

Product Name:

Screw, retaining, cutoff valve seat

Screw Material:

Steel comp 630

Screw Material Specification:

Ams5643 assn standard single material response

Bearing Surface Of Head Surface Treatment:

Passivate

Head Surface Treatment:

Passivate

Screw Surface Treatment:

Passivate

Shank Surface Treatment:

Passivate

Bearing Surface Of Head Surface Treatment Specification:

Qq-p-35 federal specification 1st treatment response

Head Surface Treatment Specification:

Qq-p-35 federal specification 1st treatment response

Screw Surface Treatment Specification:

Qq-p-35 federal specification 1st treatment response

Shank Surface Treatment Specification:

Qq-p-35 federal specification 1st treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A500d0