NSN 5305-01-430-3496

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-430-3496

3
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.334 inches and 0.354 inches
Fastener Length:
Between 0.428 inches and 0.448 inches
Head Style:
Fillister
Head Diameter:
Between 0.271 inches and 0.281 inches
Head Height:
Between 0.218 inches and 0.232 inches
Hole Diameter:
0.055 inches
Internal Drive Style:
Slot
End Application:
F-18
Thread Diameter:
0.190 inches
Hole Quantity:
2
Nonstandard Thread Pitch Diameter:
+0.1605/+0.1629 inches
Thready Qty Per Inch (tpi):
24
Screw Material:
Steel comp 1212
Screw Material Specification:
Ams5010 assn standard single material response
Bearing Surface Of Head Surface Treatment:
Cadmium
Head Surface Treatment:
Cadmium
Screw Surface Treatment:
Cadmium
Shank Surface Treatment:
Cadmium
Bearing Surface Of Head Surface Treatment Specification:

Ams2400 assn standard single treatment response

NSN 5305-01-430-3496

Machine Screw - Page 2 of 2



L	heal	Surfac	e Trea	tment S	Snecifi	cation:
г	ıeau	Suriac	e iiea	unenc	speciii	Calibii.

Ams2400 assn standard single treatment response

Screw Surface Treatment Specification:

Ams2400 assn standard single treatment response

Shank Surface Treatment Specification:

Ams2400 assn standard single treatment response

Head Hole Configuration Style:

Round

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A500d0