# NSN 5305-01-430-5421

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-430-5421



**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

#### Thread Length:

Between 1.917 inches and 2.000 inches

#### Fastener Length:

Between 1.940 inches and 2.000 inches

#### Head Style:

Pan

Head Diameter:

Between 0.716 inches and 0.740 inches

#### **Head Height:**

Between 0.244 inches and 0.261 inches

#### Internal Drive Style:

Cross recess type iii

### Thread Diameter:

0.375 inches

## Thready Qty Per Inch (tpi):

24

#### Min. Tensile Strength (psi):

160000 pounds per square inch

#### Screw Material:

Steel comp 4140 or steel comp 4340 or steel comp 8740

#### Screw Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military

specification 3rd material response

### Screw Surface Treatment:

Cadmium and chromate

#### Screw Surface Treatment Specification:

Qq-p-416, type 2, class2 federal specification all treatment responses

#### Thread Series Designator:

Unjf

#### **Specification Data:**

80205-nas606 professional/industrial association standard

Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

# Fiig:

A500d0

# NSN 5305-01-430-5421

Machine Screw - Page 2 of 2

## Mil-std (military Standard):

Mil-s-5626 spec.

