

View Online at <https://aerobasegroup.com/nsn/5305-01-431-2204>

Thread Direction:

Right-hand

Thread Length:

4.0 millimeters

Fastener Length:

Between 10.62 millimeters and 11.38 millimeters

Head Style:

Pan

Head Diameter:

Between 5.5 millimeters and 5.8 millimeters

Head Height:

Between 1.65 millimeters and 1.90 millimeters

First Diameter From Head:

Between 2.11 millimeters and 2.35 millimeters

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

7.0 millimeters

Internal Drive Style:

Cross recess type 1

Thread Diameter:

3.0 millimeters

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Pitch In Millimeters:

0.5

External Thread Tolerance Class:

6g

Externally Relieved Body Diameter Quantity:

1

Color:

Black

Material:

Iron alloy 660

Material Specification:

Ams5737 assn standard single material response

Surface Treatment:

Oxide

Surface Treatment Specification:

Mil-c-13924, cl 4 military specification single treatment response

Thread Series Designator:

M

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.