

View Online at <https://aerobasegroup.com/nsn/5305-01-431-2204>

**Thread Direction:**

Right-hand

**Thread Length:**

4.0 millimeters

**Fastener Length:**

Between 10.62 millimeters and 11.38 millimeters

**Head Style:**

Pan

**Head Diameter:**

Between 5.5 millimeters and 5.8 millimeters

**Head Height:**

Between 1.65 millimeters and 1.90 millimeters

**First Diameter From Head:**

Between 2.11 millimeters and 2.35 millimeters

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

7.0 millimeters

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

3.0 millimeters

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Thread Pitch In Millimeters:**

0.5

**External Thread Tolerance Class:**

6g

**Externally Relieved Body Diameter Quantity:**

1

**Color:**

Black

**Material:**

Iron alloy 660

**Material Specification:**

Ams5737 assn standard single material response

**Surface Treatment:**

Oxide

**Surface Treatment Specification:**

Mil-c-13924, cl 4 military specification single treatment response

**Thread Series Designator:**

M

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-13924 spec.