NSN 5305-01-431-2204

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-431-2204 **Thread Direction:** Right-hand Thread Length: 4.0 millimeters Fastener Length: Between 10.62 millimeters and 11.38 millimeters **Head Style:** Pan **Head Diameter:** Between 5.5 millimeters and 5.8 millimeters **Head Height:** Between 1.65 millimeters and 1.90 millimeters First Diameter From Head: Between 2.11 millimeters and 2.35 millimeters Distance From Largest Bearing Surface Of Head To End Of First Diameter: 7.0 millimeters **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 3.0 millimeters Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Pitch In Millimeters:** 0.5 **External Thread Tolerance Class:** 6g **Externally Relieved Body Diameter Quantity:** Color: Black Material: Iron alloy 660 **Material Specification:** Ams5737 assn standard single material response **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924, cl 4 military specification single treatment response **Thread Series Designator:** Μ Shelf Life: N/a

NSN 5305-01-431-2204

Externally Relieved Body Screw - Page 2 of 2



Unit Of Measure:	U	In	it	Of	Measure:
------------------	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.