Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-431-5193

Thread	Class:
· · · · · · · · ·	0.000

2a

**Thread Direction:** 

**Right-hand** 

**Thread Length:** 

0.688 inches

#### **Fastener Length:**

1.687 inches

#### **Head Style:**

Knurled no. 5

#### **Head Diameter:**

0.750 inches

#### **Head Height:**

0.438 inches

#### **Internal Drive Style:**

**Thread Diameter:** 

# 0.375 inches

Thready Qty Per Inch (tpi):

16

Slot

# **Criticality Code Justification:**

Zzzy

# **Externally Relieved Body Diameter Quantity:**

1

# **Special Features:**

Item must comply with requirements of defense supply center philadelphia production standard po0297nrp

# Material:

Steel comp 303

# **Material Specification:**

Astm a582 assn standard single material response

# **Test Data Document:**

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Thread Series Designator:**

Unc

# **Departure From Cited Document:**

As modified by material

# **Reference Number Differentiating Characteristics:**

Areference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing and testing specifications available at the dla icp

#### Shelf Life:

N/a

# Unit Of Measure:

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0