## NSN 5305-01-432-0412

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-432-0412

Thread Clas	SS:
3a	
Thread Dire	ection:
Right-hand	
Thread Len	gth:
0.400 inches	S
Fastener Le	ength:
Between 0.6	377 inches and 0.697 inches
Head Style:	
Pan	
Head Diam	eter:
Between 0.3	306 inches and 0.322 inches
Head Heigh	nt:
Between 0.1	105 inches and 0.115 inches
Grip Diame	ter:
Between 0.1	1625 inches and 0.1635 inches
Point Style:	
Half dog	
Internal Dri	ve Style:
Cross reces	s type 1
Thread Dia	meter:
0.164 inches	S
Grip Length	n:
0.125 inches	S
Thready Qt	y Per Inch (tpi):
32	
Special Fea	atures:
Two keyway	vs along threads 180 degrees apart, length of keyways of 0.462
Material:	
Steel comp	302 or steel comp 304 or steel comp 305 or steel comp 304l or steel comp 310 or steel comp 316
Surface Tre	eatment:
Passivate	
Surface Tre	eatment Specification:
Qq-p-35 fed	eral specification single treatment response
Thread Ser	ies Designator:
Unc	
Shelf Life:	
N/a	
Unit Of Mea	asure:
Demilitariza	ation:
No	

## NSN 5305-01-432-0412

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

