Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-432-1762

3a Thread Direction: Right-hand Thread Length: 0.750 inches Fastener Length: Between 0.845 inches and 0.875 inches Head Style: Flat chamfer Head Diameter: Between 0.550 inches and 0.562 inches Head Height: Between 0.368 inches and 0.375 inches
Right-hand Thread Length: 0.750 inches Fastener Length: Between 0.845 inches and 0.875 inches Head Style: Flat chamfer Head Diameter: Between 0.550 inches and 0.562 inches Head Height:
Thread Length: 0.750 inches Fastener Length: Between 0.845 inches and 0.875 inches Head Style: Flat chamfer Head Diameter: Between 0.550 inches and 0.562 inches Head Height:
0.750 inches Fastener Length: Between 0.845 inches and 0.875 inches Head Style: Flat chamfer Head Diameter: Between 0.550 inches and 0.562 inches Head Height:
Fastener Length:Between 0.845 inches and 0.875 inchesHead Style:Flat chamferHead Diameter:Between 0.550 inches and 0.562 inchesHead Height:
Between 0.845 inches and 0.875 inches Head Style: Flat chamfer Head Diameter: Between 0.550 inches and 0.562 inches Head Height:
Head Style: Flat chamfer Head Diameter: Between 0.550 inches and 0.562 inches Head Height:
Flat chamfer Head Diameter: Between 0.550 inches and 0.562 inches Head Height:
Head Diameter: Between 0.550 inches and 0.562 inches Head Height:
Between 0.550 inches and 0.562 inches Head Height:
Head Height:
Between 0.368 inches and 0.375 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.375 inches
Width Across Flats:
0.312 inches
Thready Qty Per Inch (tpi):
16
Min. Tensile Strength (psi):
170000 pounds per square inch
Hardness Rating:
37.0 rockwell c and 45.0 rockwell c
Color:
Black
Material:
Steel uns k03104
Material Specification:
Astm a574 assn standard single material response
Surface Treatment:
Oxide
Thread Series Designator:
Unrc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5305-01-432-1762

Socket Head Cap Screw - Page 2 of 2

Fiig: A003b0

