NSN 5305-01-432-6256

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-432-6256 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.850 inches and 0.910 inches **Fastener Length:** Between 2.160 inches and 2.190 inches **Head Style:** Double hexagon extended washer **Head Height:** 0.750 inches Width Between Flats: Between 0.743 inches and 0.752 inches **Extended Washer Diameter:** Between 1.107 inches and 1.125 inches **Extended Washer Thickness:** 0.200 inches **First Diameter From Head:** Between 0.620 inches and 0.630 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.280 inches **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.750 inches Thready Qty Per Inch (tpi): 10 **Hardness Rating:** 36.0 rockwell c and 43.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch **Externally Relieved Body Diameter Quantity:** 1 Color: Bronze or olive drab Material: Steel **Surface Treatment:**

Chromate

Surface Treatment Specification:

Mil-std-171 military standard single treatment response

NSN 5305-01-432-6256

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:
Un
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):

Mil-std-171 spec.