NSN 5305-01-432-6263

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-432-6263

| Thread Class: 2a Thread Direction: Right-hand |
|---|
| Thread Direction: Right-hand |
| Right-hand |
| • |
| |
| Thread Length: |
| Between 0.024 inches and 0.028 inches |
| Fastener Length: |
| 0.270 inches |
| Head Style: |
| Flat fillister |
| Head Diameter: |
| Between 0.190 inches and 0.210 inches |
| Head Height: |
| Between 0.015 inches and 0.025 inches |
| Shoulder Diameter: |
| 0.130 inches first shoulder and 0.140 inches first shoulder |
| Shoulder Length: |
| 0.140 inches first shoulder |
| Internal Drive Style: |
| Slot |
| Thread Diameter: |
| 0.112 inches |
| Thready Qty Per Inch (tpi): |
| 40 |
| Shoulder Shape: |
| Round first shoulder |
| Material: |
| Steel comp 304l |
| Material Specification: |
| Ams 5647, cond h975 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35, type 2 or type 8 federal specification single treatment response |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5305-01-432-6263 Shoulder Screw - Page 2 of 2



Fiig:

A003b0