NSN 5305-01-432-6748

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-432-6748 **Thread Direction:** Right-hand **Thread Length:** Between 36.1 millimeters and 39.9 millimeters Fastener Length: Between 39.10 millimeters and 39.90 millimeters **Head Style:** Flat chamfer **Head Diameter:** Between 15.67 millimeters and 16.00 millimeters **Head Height:** Between 9.81 millimeters and 10.00 millimeters **Internal Drive Style:** Hexagon **Thread Diameter:** 10.0 millimeters Width Across Flats: Between 10.02 millimeters and 10.12 millimeters Min. Tensile Strength (psi): 1220 megapascals Hardness Rating: 38.0 rockwell c and 44.0 rockwell c Minimum Yield Strength: 1100 megapascals **Thread Pitch In Millimeters:** 1.5 **External Thread Tolerance Class:** 4g6g Material: Steel property class 12.9 **Material Specification:** Din 912 national specification single material response **Surface Treatment:** Zinc and chromate **Surface Treatment Specification:** Astm b633, type 2, class 3 assn standard single treatment response **Thread Series Designator:** Μ Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-01-432-6748

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0