NSN 5305-01-432-9203

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-432-9203 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.530 inches **Fastener Length:** Between 0.890 inches and 0.920 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.258 inches and 0.305 inches **Grip Diameter:** Between 0.1890 inches and 0.1895 inches **Internal Drive Style:** Torque-set ribbed **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.365 inches and 0.385 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches top of head Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5305-01-432-9203

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0