## NSN 5305-01-433-0573

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-433-0573

View Online at https://aerobasegroup.com/nsn/5305-01-433-0573
Thread Direction:
Right-hand
Thread Length:
13.25 millimeters
Fastener Length:
16.0 millimeters
Head Style:
Pan no. 2
Head Diameter:
Between 15.73 millimeters and 16.00 millimeters
Head Height:
Between 6.78 millimeters and 7.00 millimeters
Shoulder Diameter:
9.951 millimeters first shoulder and 9.987 millimeters first shoulder
Shoulder Length:
16.00 millimeters first shoulder
Internal Drive Style:
Hexagon
Thread Diameter:
10.0 millimeters
Width Across Flats:
Between 5.020 millimeters and 5.084 millimeters
Thread Pitch In Millimeters:
1.50
External Thread Tolerance Class:
6g
Shoulder Shape:
Round first shoulder
Material:
Steel
Surface Treatment:
Zinc
Surface Treatment Specification:
Astmb633 assn standard single treatment response
Thread Series Designator:
Μ
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

## **NSN 5305-01-433-0573** Shoulder Screw - Page 2 of 2

Fiig: A003b0

