## NSN 5305-01-433-9800

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-433-9800 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.303 inches and 0.313 inches **Fastener Length:** 1.000 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.495 inches and 0.505 inches **Head Height:** Between 0.546 inches and 0.578 inches **First Diameter From Head:** Between 0.170 inches and 0.180 inches **Second Diameter From Head:** 0.250 inches **Third Diameter From Head:** Between 0.160 inches and 0.175 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.798 inches and 0.833 inches **Point Style:** Cone **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 **Externally Relieved Body Diameter Quantity:** Material: Steel comp 303 **Material Specification:** Qq-s-764 federal specification single material response **Surface Treatment: Passivate** 

. 400...410

**Surface Treatment Specification:** 

Mil-f-14072-e300 military specification single treatment response

**Thread Series Designator:** 

Unc

## NSN 5305-01-433-9800

Externally Relieved Body Screw - Page 2 of 2



N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):

Shelf Life:

Mil-f-14072-e300 spec.