## NSN 5305-01-434-0876

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-434-0876

Thread Class:			
3a			
Thread Direction:			
Right-hand			
Thread Length:			
0.250 inches			
Fastener Length:			
Between 0.281 inches and 0.312 inches			
Head Style:			
Flat countersunk			
Head Diameter:			
Between 0.125 inches and 0.176 inches			
Locking Feature:			
Strip			
Internal Drive Style:			
Torque set			
Thread Diameter:			
0.190 inches			
Thready Qty Per Inch (tpi):			
32			
Min. Tensile Strength (psi):			
160000 pounds per square inch			
Countersink Angle:			
Between 99.0 degrees and 101.0 degrees			
Screw Material:			
Titanium alloy uns r56400			
Locking Feature Material:			
Plastic polyamide			
Screw Material Specification:			
Ams 4928 assn standard single material response and ams 4967 assn standard single material response			
Locking Feature Material Specification:			
Mil-f-18240 military specification single material response			
Bearing Surface Of Head Surface Finish:			
32.0 microinches			
Shank Surface Finish:			
32.0 microinches			
Thread Surface Finish:			
32.0 microinches			
Thread Series Designator:			
Unjf			
Shelf Life:			
N/a			

## NSN 5305-01-434-0876

Machine Screw - Page 2 of 2



 :4	$\sim$	Measure:
 nit	l IT	MESCITE.

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-f-18240 spec.