## NSN 5305-01-434-2286

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-434-2286 **Thread Direction:** Right-hand Thread Length: Between 3.75 millimeters and 4.25 millimeters Fastener Length: Between 9.62 millimeters and 10.38 millimeters **Head Style:** Pan no. 2 **Head Diameter:** Between 5.5 millimeters and 5.8 millimeters **Head Height:** Between 1.52 millimeters and 1.98 millimeters First Diameter From Head: 2.23 millimeters Distance From Largest Bearing Surface Of Head To End Of First Diameter: 7.0 millimeters **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 3.0 millimeters **Thread Pitch In Millimeters:** 0.5 **External Thread Tolerance Class: Externally Relieved Body Diameter Quantity:** 1 Color: Black Material: Iron alloy 660 **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-13924 cl 4 military specification all treatment responses **Thread Series Designator:** М Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## NSN 5305-01-434-2286

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

spec.